

NAME

mag – computes TeX fontsizes and magsteps

SYNOPSIS

mag [-R*dpi*] *magstep* . . .

mag [-r] [-R*dpi*] *fontsize* . . .

DESCRIPTION

delim \$\$ This tool calculates fontsizes given magsteps. TeXfonts are provided as true sized fonts or as magnifications. The fontsize of a true sized font equals the resolution of the printer (ex. 300). The fontsize of a font magnified n times equals: $1.2^n \times 300$ rounded to its nearest integer value. Fontnames for TeX fonts normally consists of the name (*cmr*), pointsize (*10*), type (*pk*) and fontsize (*360*), for example: *cmr10.360pk*.

EXAMPLES

The result of *mag -R240 -2 0 0.5 1* will be:

```
167 240 263 288
```

The inverse function is computed with the *-r* option. The result of *mag -r -R240 167 240 263 288* will be the fontsteps:

```
-2 0 0.5 1
```

The UNIX shells allow command substitution. One can write:

```
mag -r -R240 `mag -R240 -2 0 0.5 1`
```

DATE

18 December, 1989

AUTHOR

Piet Tutelaers

University of Technology Eindhoven

Maintained in TeX Live; please send bug reports or other correspondence to tex-k@tug.org (<http://lists.tug.org/tex-k>).